


INTERIOR FIXTURE IP20

DLT S (M)



Frames



DLT S

Technical Specifications

Approvals:	According to the rules of relevant classification societies, UL 595, UL 924 and CSA approved.	Cable Entry:	All have 20.5 mm/.81 in. knockouts in the ends.
Materials:	Main body of electro-galvanized steel plate. Stove enamelled white epoxy powder finish. Extruded aluminum frame.	Wiring:	Flexible heat resistant wiring. Through wiring feature standard.
Diffuser:	Glamox BatWing (BW) and Darklight (DL) louvre of glamoxed aluminum with a clear acrylic finish.	Voltage & Frequency:	Standard 120V/220V, 60Hz (Others on request).
Emergency Lights:	Available with integrated emergency power supply units (90 minutes standard) or incandescent emergency socket.	Option Equipment:	<ol style="list-style-type: none"> 1) Electronic ballasts and dimming ballast. 2) Prismatic Acrylic diffuser (FR1). 3) Opal Acrylic diffuser (FR2). 4) External junction box fixed to main body
Mounting:	Direct to ceiling.	Subject to technical modifications without notification. Consult factory for verification.	

Types and Dimensions

Type	Watt	Length (mm/in)	Width (mm/in)	Height (mm/in)	Weight (kg/lbs)
DLT S 312 217 FR1	2/17	660/25.94	332/13.03	96/3.75	5.0/11.0
DLT S 312 217 FR2	2/17	660/25.94	332/13.03	96/3.75	5.0/11.0
DLT S 312 220 FR1	2/20	660/25.94	332/13.03	96/3.75	5.0/11.0
DLT S 312 220 FR2	2/20	660/25.94	332/13.03	96/3.75	5.0/11.0
DLT S 312 232 FR1	2/32	1270/49.91	332/13.03	96/3.75	8.06/19.0
DLT S 312 232 FR2	2/32	1270/49.91	332/13.03	96/3.75	8.06/19.0
DLT S 312 240 FR1	2/40	1270/49.91	332/13.03	96/3.75	8.06/19.0
DLT S 312 240 FR2	2/40	1270/49.91	332/13.03	96/3.75	8.06/19.0
DLT S 312 332 FR1	3/32	1270/49.91	332/13.03	96/3.75	8.06/19.0