

GXPN

Hazardous Area Luminaire, Surface

IP67	Battery Backup	120V/60Hz 120-277V/50-60Hz
Class 1 Div. 2	Class 1 Zone 2	

Technical Specification

Application: Hazardous areas: decks, process areas, machinery spaces, etc. Class 1 Division 2 and Class 1 Zone 2.

Approvals: Class I, Division 2, Groups A, B, C, D. UL 844, UL 924, and CSA C22.2 No. 137-M1981.

Protection: IP67

Housing: Aluzinc sheet steel or stainless steel, deep drawn, seamless.

Finish: Epoxy powder coated, white RAL 9016.

Diffuser: Clear polycarbonate.

Electrics: Flexible wiring, heat resistant to 105°C; through wiring up to 15 A.

Cable entry: One ½" conduit hub and one blind plug at each end.

Lamp base: G13

Light source(not included): Fluorescent lamp; 17/32W T8 with electronic ballast, 20/40W T12 with magnetic ballast.

Battery backup: Optional 90 minute battery backup. 500-600 lumens for 90 minutes at 20°C. Other configurations available upon request.

Charge time after full discharge: 24 hours.

Mounting: 2 brackets for direct mounting to bulkhead or deckhead. Custom mounting brackets are also available.

Remarks: Low temperature ballast is available upon request.

